

Looking for Real Exam Questions for IT Certification Exams!

We guarantee you can pass any IT certification exam at your first attempt with just 10-12 hours study of our guides.

Our study guides contain actual exam questions, you will get word to word same on your actual test; accurate answers with detailed explanation verified by experts and all graphics and drag-n-drop exhibits shown just as on the real test.

To test the quality of our guides, you can download the one-third portion of any guide from <http://www.certificationking.com> absolutely free.

Besides, we also offer complete version of following exams absolutely free. You can start your certification from these free guides and if you are satisfied you can buy the rest

- ◆ Microsoft: 70-270, 70-305 ◆ Cisco: 642-901 ◆ Oracle: 1Z0-007, 200 ◆ CompTIA: 220-601
- ◆ SUN: 310-011, 310-043 ◆ Citrix: 1Y0-A01, 1Y0-256 ◆ CIW: 1D0-420 ◆ Novell: 50-686
- ◆ Adobe: 9A0-029 ◆ Apple: 9L0-005, 9L0-505 ◆ Avaya: 132-S-100 ◆ Cognos: COG-105
- ◆ CWNP: PW0-100 ◆ EMC: E20-001 ◆ Hyperion: 4H0-002 ◆ HP: HP0-771, HP0-J24
- ◆ IBM: 000-253, 000-700 ◆ Juniper: JN0-100, JN0-201 ◆ Lotus: LOT-737
- ◆ Nortel: 920-803 ◆ SAS: A00-201 ◆ SNIA: S10-100 ◆ Sybase: 510-015
- ◆ Symantec: 250-101 ◆ TeraData: NR0-011

For pricing and placing order, please visit <http://certificationking.com/order.html>

We accept all major credit cards through www.paypal.com

For other payment options and any further query, feel free to mail us at info@certificationking.com

Exam Name:	SAS Base Programming for SAS (r) 9		
Exam Type:	SAS		
Exam Code:	A00-211	Total Questions:	127

Question: 1

The SAS data set SASUSER.HOUSES contains a variable PRICE which has been assigned a permanent label of "Asking Price". Which SAS program temporarily replaces the label "Asking Price" with the label "Sale Price" in the output?

- A. proc print data = sasuser.houses; label price = "Sale Price"; run;
- B. proc print data = sasuser.houses label; label price "Sale Price"; run;
- C. proc print data = sasuser.houses label; label price = "Sale Price"; run;
- D. proc print data = sasuser.houses; price = "Sale Price"; run;

Answer: C

Question: 2

The following GAS program is submitted:

```
data work.empsalary;
set work.people (in = inemp)
work.money (in = insal);
if insal and inemp;
run;
```

The SAS data set WORKPEOPLE has 5 observations, and the data set WORKMONEY has 7 observations. How many observations will the data set WORK.EMPSALARY contain?

- A. 0
- B. 5
- C. 7
- D. 12

Answer: A

Question: 3

The following SAS program is submitted:

```
data work.accounting;
set work.dept1 work.dept2;
jobcode = 'FA1';
length jobcode $ 8;
run;
```

A character variable named JOBCODE is contained in both the WORK.DEPT1 and WORK.DEPT2 SAS data sets. The variable JOBCODE has a length of 5 in the WORK.DEPT1 data set and a length of 7 in the WORK.DEPT2 data set. What is the length of the variable JOBCODE in the output data set?

- A. 3
- B. 5
- C. 7
- D. 8

Answer: B

Question: 4

Given the SAS data set SASDATA.TWO:

Exam Name:	SAS Base Programming for SAS (r) 9		
Exam Type:	SAS		
Exam Code:	A00-211	Total Questions:	127

SASDATA.TWO

X	Y
--	---
5	2
3	1
5	6

The following SAS program is submitted:

```
data sasuser.one two sasdata.three;
set sasdata two;
if x = 5 then output sasuser.one;
else output sasdata two;
run;
```

What is the result?

- A. data set SASUSER.ONE has 5 observations
data set SASUSER.TWO has 5 observations
data set WORK.OTHER has 3 observations
- B. data set SASUSER.ONE has 2 observations
data set SASUSER.TWO has 2 observations
data set WORK.OTHER has 1 observations
- C. data set SASUSER.ONE has 2 observations
data set SASUSER.TWO has 2 observations
data set WORK.OTHER has 5 observations
- D. No data sets are output.
The DATA step fails execution due to syntax errors.

Answer: A

Question: 5

The following SAS program is submitted:

```
footnote 1 'Sales Report for Last Month';
footnote2 'Selected Products Only';
footnote3 'All Regions';
footnote4 'All Figures in Thousands of Dollars';
proc print data = sasuser.shoes;
footnote2 'All Products';
run;
```

Which footnote(s) is/are displayed in the report?

- A. All Products
- B. Sales Report for Last Month All Products
- C. All Products All Regions All Figures in Thousands of Dollars
- D. Sales Report for Last Month All Products All Regions All Figures in Thousands of Dollars

Answer: B

Question: 6

Given the raw data record DEPT:

----|----10---|----20---|----30

Exam Name:	SAS Base Programming for SAS (r) 9		
Exam Type:	SAS		
Exam Code:	A00-211	Total Questions:	127

Printing 750

The following SAS program is submitted:

```
data bonus;
infile 'dept';
inputdept$ 1-11 number 13- 15;
<insert statement here>
run;
```

Which SAS statement completes the program and results in a value of 'Printing750' for the DEPARTMENT variable?

- A. department = dept || number;
- B. department = left(dept) || number;
- C. department = trim(dept) || number;
- D. department = trim(dept) || put(number,3.);

Answer: D

Question: 7

The following SAS program is submitted:

```
data one;
address1 = '214 London Way';
run;
data one;
set one;
address = tranwrd(address1, 'Way', 'Drive'); run;
What are the length and value of the variable ADDRESS?
```

- A. Length is 14; value is '214 London Dri'.
- B. Length is 14; value is '214 London Way'.
- C. Length is 16; value is '214 London Drive'.
- D. Length is 200; value is '214 London Drive'.

Answer: D

Question: 8

The following SAS program is submitted:

```
data work.sets;
do until (prod gt 6);
prod + 1;
end;
run;
```

What is the value of the variable PROD in the output data set?

- A. 6
- B. 7
- C. 8
- D. (missing numeric)

Answer: B

Exam Name:	SAS Base Programming for SAS (r) 9		
Exam Type:	SAS		
Exam Code:	A00-211	Total Questions:	127

Question: 9

Given the SAS data sets EMPLOYEE and SALARY:

EMPLOYEE		SALARY	
Fname	age	name	salary
Bruce	30	Bruce	25000
Dan	40	Bruce	35000
		Dan	25000

The following SAS program is submitted:

```
data work.empdata;
<insert MERGE statement here>
by fname;
totsal + salary;
run;
```

Which MERGE statement correctly completes the program?

- A. merge employee
salary rename = fname = name;
- B. merge employee
salary rename(name = fname);
- C. merge employee
salary (rename = (fname = name));
- D. merge employee
salary (rename = (name = fname));

Answer: D

Question: 10

Which program displays a listing of all data sets in the SASUSER library?

- A. proc contents lib = sasuser.all; run;
- B. proc contents data = sasuser.all; run;
- C. proc contents lib = sasuser._all_; run;
- D. proc contents data = sasuser._all_; run;

Answer: D

Question: 11

The following SAS program is submitted:

```
proc sort data = work.employee;
by descending fname;
proc sort data = work.salary;
by descending fname;
data work.empdata;
merge work.employee
work.salary;
by fname;
run;
```

Why does the program fail to execute?

Exam Name:	SAS Base Programming for SAS (r) 9		
Exam Type:	SAS		
Exam Code:	A00-211	Total Questions:	127

- A. The SORT procedures contain invalid syntax.
- B. The merged data sets are not permanent SAS data sets.
- C. The RUN statement was omitted after each of the SORT procedures.
- D. The data sets were not merged in the order by which they were sorted.

Answer: D

Question: 12

The following SAS program is submitted:

```
data work.sales;
do year = 1 to 5;
do month=1 to 12;
x+1;
output
end;
end;
run;
```

How many observations are written to the WORK SALES data set?

- A. 0
- B. 1
- C. 5
- D. 60

Answer: D

Question: 13

Given the following raw data record:

```
----|----10---|----20---|----30
```

son Travis,

The following output is desired:

```
Obs    relation  firstame
1      son      Travis
```

Which SAS program correctly reads in the raw data?

- A. data family (dlm = ','); infile 'file specification'; input relation \$ firstame \$; run;
- B. options dlm = ','; data family; infile 'file specification'; input relation \$ firstame \$; run;
- C. data family; infile 'file specification' dlm = ','; input relation \$ firstame \$; run;
- D. data family; infile 'file specification'; input relation \$ firstame \$ / dim = ','; run;

Answer: C

Question: 14

Given the SAS data set AGES:

```
AGES
AGE
-----
```

The variable AGE contains character values. The following SAS program is submitted:

Page 5 of 57		
---------------------	--	--

Exam Name:	SAS Base Programming for SAS (r) 9		
Exam Type:	SAS		
Exam Code:	A00-211	Total Questions:	127

```
data subset;
set ages;
where age > 12;
run;
```

How many observations are written out to the data set SUBSET?

- A. 0
- B. 1
- C. 2
- D. 3

Answer: A

Question: 15

Given the SAS data set PRICES:

```
PRICES
prodid price producttype sales returns
K12S 5.10 NETWORK 15 2
B132S 2.34 HARDWARE 300 10
R18KY21.29 SOFTWARE 25 5
3KL8BY 6.37 HARDWARE 125 15
DY65DW 5.60 HARDWARE 45 5
DGT23 4.55 HARDWARE 67 2
```

The following SAS program is submitted:

```
data hware inter soft;
set prices (keep = producttype price);
if price le 5.00;
if producttype = 'HARDWARE' then output HWARE;
else if producttype = 'NETWORK' then output INTER;
else if producttype = 'SOFTWARE' then output SOFT;
run;
```

How many observations does the HWARE data set contain?

- A. 0
- B. 2
- C. 3
- D. 4

Answer: B

Question: 16

The following SAS program is submitted:

```
data work.accounting;
set work.department;
length jobcode $ 12;
jobcode='FAI';
run;
```

Exam Name:	SAS Base Programming for SAS (r) 9		
Exam Type:	SAS		
Exam Code:	A00-211	Total Questions:	127

The WORK.DEPARTMENT data set contains a character variable named JOBCODE with a length of 5.

What is the result?

- A. The length of the variable JOBCODE is 3.
- B. The length of the variable JOBCODE is 5.
- C. The length of the variable JOSBODE is 12.
- D. The program fails to execute due to errors.

Answer: B

Question: 17

Which ODS statement option terminates output being written to an HTML file?

- A. END
- B. QUIT
- C. STOP
- D. CLOSE

Answer: D

Question: 18

The SAS data set PETS is sorted by the variables TYPE and BREED.

The following SAS program is submitted:

```
proc print data = pets;
var type breed;
sum number;
run;
```

What is the result?

- A. The SUM statement produces only a grand total of NUMBER.
- B. The SUM statement produces only subtotals of NUMBER for each value of TYPE.
- C. The SUM statement produces both a grand total of NUMBER and subtotals of NUMBER for each value of TYPE.
- D. Nothing is produced by the SUM statement; the program fails to execute.

Answer: A

Question: 19

The following SAS program is submitted:

```
data work.passengers;
if OrigPassengers = then
OrigPassengers = 100;
TransPassengers = 100;
OrigPassengers =
TotalPassengers = sum (OrigPassengers, TransPassengers) +0;
run;
```

What is the value of the TOTALPASSENGERS variable in the output data set?

- A. 0

Exam Name:	SAS Base Programming for SAS (r) 9		
Exam Type:	SAS		
Exam Code:	A00-211	Total Questions:	127

- B. 100
- C. 200
- D. (missing numeric value)

Answer: B

Question: 20

Given the SAS data set PRICES:

PRICES

ProdId	price	producttype	sales	returns
K125	5.10	NETWORK	15	2
B132S	2.34	HARDWARE	300	10
R18KY2	1.29	SOFTWARE	25	5
3KL8BY	6.37	HARDWARE	125	15
DY65DW	5.60	HARDWARE	45	5
DGTY23	4.55	HARDWARE	67	2

The following SAS program is submitted:

```
data hware inter cheap;
set prices(keep = producttype price);
if producttype = 'HARDWARE' then output hware; else if producttype = 'NETWORK' then output
inter; if price le 5.00;
run;
```

How many observations does the HWARE data set contain?

- A. 0
- B. 2
- C. 3
- D. 4

Answer: D

Question: 21

The following SAS program is submitted:

```
data work.sales;
do year = 1 to 5;
do month = 1 to 12;
x+ 1;
end;
end;
run;
```

How many observations are written to the WORK.SALES data set?

- A. 0
- B. 1
- C. 5
- D. 60

Answer: B

Question: 22

Exam Name:	SAS Base Programming for SAS (r) 9		
Exam Type:	SAS		
Exam Code:	A00-211	Total Questions:	127

The following SAS program is submitted:

```
data work.totalsales (keep = monthsales{12});
set work.monthlysales (keep = year product sales);
array monthsales{12};
do i = 1 to 12; monthsales{i} = sales;
end;
run;
```

The program fails execution due to syntax errors. What is the cause of the syntax error?

- A. The variable MONTHSALES does not exist.
- B. An array cannot be referenced on a KEEP data set option.
- C. The KEEP= data set option should be (KEEP = MONTHSALES).
- D. The KEEP= data set option should be the statement KEEP MONTHSALES{12}.

Answer: B

Question: 23

Given the SAS data set EMPLOYEES:

```
EMPLOYEES
NAME  SALARY
-----
Innis  60000
Jolli  50000
Ellis  55000
Liu    45000
```

The following SAS program is submitted:

```
proc print data = employees; where name like '_i%';
run;
```

What is contained in the output?

- A. Liu only
- B. Innis and Ellis only
- C. Innis, Ellis, and Liu only
- D. Innis, Jolli, Ellis, and Liu

Answer: A

Question: 24

Given the SAS data set ONE:

```
ONE
Obs  Dte
-----
1    09JAN2005
2    12JAN2005
```

The following SAS program is submitted:

```
data two;
set one;
```

Exam Name:	SAS Base Programming for SAS (r) 9		
Exam Type:	SAS		
Exam Code:	A00-211	Total Questions:	127

```

day = <insert expression here>;
format dte date9.;
run;

```

The data set TWO is created:

```

TWO
Obs    Dte          Day
1      09JAN2005    1
12     JAN2005      4

```

Which expression successfully completed the program and created the variable DAY?

- A. day(dte)
- B. weekday(dte)
- C. dayofweek(dte)
- D. datdif(dte,'01jan2005'd,'act/act')

Answer: B

Question: 25

Read the table:

Obs	style	sqfeet	bedrooms	baths	street	price
1	RANCH	1250	2	1.0	Sheppard Avenue	\$64,000
2	SPLIT	1190	1	1.0	Rand Street	\$65,850
3	CONDO	1400	2	1.5	Market Street	\$80,050
4	TWOSTORY	1810	4	3.0	Garris Street	\$107,250
5	RANCH	1500	3	3.0	Kemble Avenue	\$86,650
6	SPLIT	1615	4	3.0	West Drive	\$94,450
7	SPLIT	1305	3	1.5	Graham Avenue	\$73,650
8	CONDO	1390	3	2.5	Hampshire Avenue	\$79,350
9	TWOSTORY	1040	2	1.0	Sanders Road	\$55,850
10	CONDO	2105	4	2.5	Jeans Avenue	\$127,150
11	RANCH	1535	3	3.0	State Highway	\$89,100
12	TWOSTORY	1240	2	1.0	Fairbanks Circle	\$69,250
13	RANCH	720	1	1.0	Nicholson Drive	\$34,550
14	TWOSTORY	1745	4	2.5	Highland Road	\$102,950
15	CONDO	1860	2	2.0	Arcata Avenue	\$110,700

Given the SAS data set SASUSER.HOUSES:

```

Obs    style    bedrooms    baths    price    sqteet    street
1      CONDO      2          1.5     80050    1200     MAIN
2      CONDO      3          2.5     79350    1300     ELM
3      CONDO      4          2.5     127150   1400     OAK
4      CONDO      2          2.0     110700   1100     FIFTH
5      TWOSTORY    4          3.0     107250   2100     SECOND
6      TWOSTORY    2          1.0     55650    1600     WEST
7      TWOSTORY    2          1.0     69250    1450     NORTH
6      TWOSTORY    4          2.5     102950   2000     SOUTH

```

The following SAS program is submitted:

```

proc report data = sasuser.houses nowd headline;
column style price;

```

Exam Name:	SAS Base Programming for SAS (r) 9		
Exam Type:	SAS		
Exam Code:	A00-211	Total Questions:	127

```

where price lt 100000;
<insert DEFINE statement here>
define price / mean width = 9 format = dollar12.;
title;
run;

```

The following output is desired:

```

style           price
-----
CONDO           $79,700
TWOSTORY        $62550

```

Which DEFINE statement completes the program and produces the desired output?

- A. define style / width = 9;
- B. define style / orderwidth = 9;
- C. define style / group width = 9;
- D. define style / display width = 9;

Answer: C

Question: 26

Given the SAS data set WORKAWARDS:

```

WORK.AWARDS
FNAME      POINTS      MONTH
-----
Amy         2           4
Amy         1           7
Gerard      3           3
Wang        3           3
Wang        1          12
Wang        1           8

```

The following SAS program is submitted:

```

proc sort data = work.awards;
by descending fname points;
run;

```

How are the observations sorted?

A. ENAME POINTS MONTH

```

Wang      3      3
Wang      1     12
Wang      1      8
Gerard    3      3
Amy       2      4
Amy       1      7

```

B. ENAME POINTS MONTH

```

Amy       2      4
Amy       1      7
Gerard    3      3
Wang      3      3
Wang      1      8

```

Exam Name:	SAS Base Programming for SAS (r) 9		
Exam Type:	SAS		
Exam Code:	A00-211	Total Questions:	127

```

      Wang      1      12
C. ENAME POINTS MONTH
      Wang      3      3
      Wang      1      8
      Wang      1     12
      Gerard    3      3
      Amy       2      4
      Amy       1      7
D. ENAME POINTS MONTH
      Wang      1     12
      Wang      1      8
      Wang      3      3
      Gerard    3      3
      Amy       1      7
      Amy       2      4

```

Answer: D

Question: 27

The following SAS program is submitted:

```

libname temp 'SAS data library';
data work.new;
set temp.jobs;
format newdate mmddw10.;
mdate = month(newdate);
ddate = weekday(newdate);
run;
proc print data = work.new; run;

```

The variable NEWDATE contains the SAS date value for April 15, 2005. What output is produced if April 15, 2005 falls on a Friday?

- A. Obsnewdate mdate ddate
104/15/2005 APR 6
- B. Obs newdate mdate ddate
104/15/2005 4 6
- C. Obs newdate mdate ddate
104/15/2005 APR 7
- D. Obs newdate mdate ddate
104/15/2005 4 7

Answer: B

Question: 28

Given the contents of the raw data file PRODUCT:

```
----|----10---|----20---|----30
```

```
24613 $25.31
```

The following SAS program is submitted:

```

data inventory;
infile 'product';
input idnum 5. @10 price;
run;

```

Exam Name:	SAS Base Programming for SAS (r) 9		
Exam Type:	SAS		
Exam Code:	A00-211	Total Questions:	127

What is the value of the PRICE variable?

- A. 25.31
- B. \$25.31
- C. . (missing numeric value)
- D. No value is stored.

Answer: C

Question: 29

The following SAS program is submitted:

```
proc contents data = sashelp.class varnum; quit;
```

What does the VARNUM option print?

- A. a list of variable names
- B. the total number of variables
- C. a list of the variables in alphabetic order
- D. a list of the variables in the order they were created

Answer: D

Question: 30

The following SAS program is submitted:

```
data test;
set chemists;
itjobcode = 'Chem2'
then description = 'Senior Chemist';
else description = 'Unknown';
run;
```

The value for the variable JOBCODE is:

JOBCODE

chem2

What is the value of the variable DESCRIPTION?

- A. chem2
- B. Unknown
- C. Senior Chemist
- D. ' ' (missing character value)

Answer: B

Question: 31

Given the AIRPLANES data set

AIRPLANES

TYPE MPG

F-18 105

Exam Name:	SAS Base Programming for SAS (r) 9		
Exam Type:	SAS		
Exam Code:	A00-211	Total Questions:	127

C-130 25
Harrier 75
A-6 110

The following SAS program is submitted:

```
data gt100;
set airplanes(keep = type mpg load);
load = mpg * 150;
run;
```

The program fails to execute due to syntax errors.

What is the cause of the syntax error?

- A. MPG is not a numeric variable.
- B. LOAD is not a variable in the data set GT100.
- C. LOAD is not variable in the data set AIRPLANES.
- D. LOAD must be defined prior to the SET statement.

Answer: C

Question: 32

Given the raw data file EMPLOYEE:

```
----|----1 0---|----20---|----30
```

```
Ruth 39 11
Jose 32 22
Sue 30 33
John 40 44
```

The following SAS program is submitted:

```
data test;
infile 'employee';
input employee_name $ 1-4;
if employee_name = 'Ruth' then input idnum 10-11;
else input age 7-8;
run;
```

What value does the variable IDNUM contain when the name of the employee is "Ruth"?

- A. 11
- B. 22
- C. 33
- D. (missing numeric value)

Answer: B

Question: 33

The following SAS program is submitted:

```
data temp.x;
set sasuser.y;
run;
```